







# CHIPPING HAMMER TFC-200F

This fluxchipper by Toku has a quick-change chisel retainer. Extremely high impactfrequency. For industrial use, chipping of welding seams.

**Characteristics:**

- Ergonomic design, well balanced
- Compact and lightweight
- Low on noise and vibrationlevels

**Related products**

-  **CB40906180**  
Chisel Bend TL=180 W=50
-  **CB40904180**  
Chisel Bend TL=180 W=35
-  **CB40901180**  
Moil Point TL=180
-  **CB40903180**  
Wide Chisel TL=180 W=35
-  **CB40902180**  
Flat Chisel TL= 180 B=19
-  **CB40905180**  
50Mm Wide Chisel,L=180Mm



**Specifications**

<b>Brand</b>	<b>Toku</b>
<b>Airconsumption (l/s)</b>	<b>4,1</b>
<b>Weight (kg)</b>	<b>1,5</b>
<b>Shank size (mm)</b>	<b>V<sup>12,7</sup> x R<sup>9,5</sup></b>
<b>Airconnection</b>	<b>PT 1/4"</b>
<b>Airpress max. (MPa)</b>	<b>0,63</b>
<b>mm A</b>	<b>189</b>
<b>mm B</b>	<b>40</b>
<b>Stroke (mm)</b>	<b>10</b>
<b>Strokes per minute</b>	<b>12000</b>
<b>Energy (J/Stroke)</b>	<b>1,1</b>
<b>Hosediameter (mm)</b>	<b>6,5</b>
<b>Piston (mm)</b>	<b>20</b>
<b>Safety standard</b>	<b>EN ISO 11148-4</b>
<b>Vibration standard</b>	<b>EN ISO 28927-9</b>
<b>Vibration value (m/s<sup>2</sup>)</b>	<b>28,7</b>
<b>Vibration uncertainty (m/s<sup>2</sup>)</b>	<b>0,79</b>
<b>Sound standard</b>	<b>ISO 15744</b>
<b>Sound pressure (dB(A))</b>	<b>90</b>
<b>Sound power (dB(A))</b>	<b>101</b>
<b>Sound uncertainty (dB(A))</b>	<b>3</b>
<b>EAN</b>	<b>8717981148370</b>

