

# SCREWDRIVER WITH CLUTCH RR-06SP

This RED ROOSTER screwdriver has an adjustable clutch mechanism. Developed for Automotive Aftermarket use. Composite body in ergonomic shape to support the operator.

Characteristics:

- \* Pistol model with trigger-start, well balanced
- \* Compact and lightweight
- \* Exhaust through grip, with silencer

## Related products



AC30A-F03E-B  
Modular FRL Unit

## Related accessories

EH-701SUB

Hose set noise suppressor



ATLUB  
Air Tool Oil, 1 litre



## Specifications

Brand	RedRooster
Bolt capacity (mm)	6
RPM	800
Torque (Nm)	5,0 - 16
Airconsumption (l/s)	10,0
Weight (kg)	1,40
Hexagon	1/4"
Airconnection	PT 1/4"
Airpress max. (MPa)	0,63
mm A	214
mm C	165
Hosediameter (mm)	10
Execution	Pistol
Safety standard	EN ISO 11148-6
Vibration standard	EN ISO 28927-2
Vibration value (m/s <sup>2</sup> )	0,2
Vibration uncertainty (m/s <sup>2</sup> )	0,12
Sound standard	ISO 15744
Sound pressure (dB(A))	87
Sound power (dB(A))	98
Sound uncertainty (dB(A))	3
EAN	8717981197484

