

50MM MINI DISC SANDER KIT

RRS-60152K

This mini-sander of RED ROOSTER has a ROLOC system for quick and sure exchange of sanding discs. The RPM is adjustable. Very simple and robust construction

Characteristics:

- * Ergonomic design, well balanced
- * Exhaust air silenced through grip
- * Wide starter for operator comfort
- * Body in composite material
- * Lightweight
- * In blowmolded case, including 10 discs each of grain 80, grain 100 and grain 120



Specifications

| | |
|--|----------------|
| Brand | RedRooster |
| RPM | 15000 |
| Airconsumption (l/s) | 4,9 |
| Weight (kg) | 0,54 |
| Airconnection | PT 1/4" |
| Airpress max. (MPa) | 0,63 |
| mm A | 100 |
| mm B | 140 |
| Hosediameter (mm) | 10 |
| Spindle | 1/4" - 20 |
| Power (kW) | 0,3 |
| Safety standard | EN ISO 11148-8 |
| Excenter stroke (mm) | - |
| Vibration standard | EN ISO 28927-1 |
| Vibration value (m/s²) | 3,11 |
| Vibration uncertainty (m/s²) | 0,8 |
| Sound standard | ISO 15744 |
| Sound pressure (dB(A)) | 80 |
| Sound power (dB(A)) | 91 |
| Sound uncertainty (dB(A)) | 3 |
| EAN | 8717981325610 |

