

AIR CHAIN HOISTS 250 KG TCR-600250PE

Related products



6,3X19,1RS60

Chain RSA60 DIN 5684-6



42-02-28-VRD

Pendant Valve Assy TCR/TMH



6,3X19,1RTS

Chain RTS EN 818-7



Specifications

| | |
|---|-----------------------|
| Brand | RedRooster |
| Number of chain falls | 1 |
| Lowering speed full load (m/min) | 17,9 |
| Lowering speed 0-load (m/min) | 13 |
| Weight incl. 3m lift (kg) | 31,1 |
| Lifting speed full load (m/min) | 10,5 |
| Lifting speed 0-load (m/min) | 20,5 |
| Chain weight (kg/m) | 0,8 |
| Chain (mm) | 6,3 x 19,1 |
| Chainbag/Chainbucket | + |
| Loadlimiter | * |
| Airconnection | 1/2" BSPT |
| Airpress max. (MPa) | 0,63 |
| mm A | 460 |
| mm B | 212 |
| mm C | 115 |
| mm D | 51 |
| mm E | 156 |
| mm F | 186 |
| mm G | 29 |
| mm H | 40 |
| mm I | 29 |
| mm J | 29 |
| mm X | 100 |
| mm Z | 250 |
| Hosediameter (mm) | 13 |
| SMC Airtreatment unit | AC40-F04DM-8-B |
| Capacity (kg) | 250 |
| Air consumption lifting (l/s) | 25 |
| Air consumption lowering (l/s) | 27 |
| EAN | 8717981180158 |

