

HIGH TORQUE GEAR WRENCH 900 NM RRI-BEC090S

















RED ROOSTER Cordless high torque geared wrench. Very well suited for assembly applications with a need of good torque accuracy. Especially in areas where cables and hoses impede handling flexibility. Contactless trigger and forward / reverse switch for a long lifetime. Version with two-hand safety control. This gear wrench has an extremely high speed.

Characteristics:

- Brushless motor
- 36 Volt Lithium-Ion battery
- LED status indicates OK - NOK - REVERSE - BATTERY LOW
- Adjustable torque in 50 steps
- Display shows torque and setting
- automatic reaction arm release
- Tightening data retrievable via USB interface

Standard reaction arm is included. Batteries, charger and other accessories must be ordered separately.

Related accessories

-  61022-GW010
Nose extension for Truck and Bus wheels
-  31022-GW005
Sliding Reaction Plate RRI-BEC090/120
-  SW40-283-0102
Hanger
-  31084-360F
36V Charger
-  33257-RRI-BEC090
Standard Reaction Bar RRI-BEC090/120
-  31022-GW001
Reaction Bar RRI-BEC025-250
-  31022-GW003
Single-Sided Reaction Plate RRI-BEC090/120
-  31022-GW010
Reaction Bar RRI-BEC025-250
-  31022-GW002
Reaction Bar Adapter RRI-BEC090/120
-  BW110
Back Up Wrench 12-Pt A/F 41 mm, max 4745 Nm, DOESR-2
-  Ret Ring
-  Koffer RRI-BEC090
-  Case RRI-BEC090
-  31022-GW009
Reaction Bar RRI-BEC025-250
-  31022-GW004
Double-Sided Reaction Plate RRI-BEC090/120
-  31022-GW018
Reaction Welding Ring RRI-BEC090/120



Specifications

Brand	RedRoosterIndustrial
Square Drive	3/4"
Bolt capacity (mm)	16 ~ 27
RPM	88 / 15
Torque (Nm)	180 ~ 900
Weight w/o battery (kg)	4,1
mm A	145
mm B	75
mm C	319
mm D	228
mm E	265
mm F	Ø 68,5
mm L	54
Battery voltage (Volt)	36
Battery type Li-ion....(Ah)	5,0
Vibration standard	EN ISO 28927-2
Vibration value (m/s ²)	1
Vibration uncertainty (m/s ²)	1,5
Sound standard	ISO 15744
Sound pressure (dB(A))	82
Sound uncertainty (dB(A))	3
EAN	8717981454457

