

125MM PALM ORBITAL SANDER RRI-5125-2CV

This RED ROOSTER palm sander is vibration-reduced. The body has a rubber cover for maximum grip. The simplicity of the construction results in a reliable tool.
Applications in: Car-bodywork, metal- and woodworking industry.

Characteristics:

- * Ergonomic design, well balanced.
- * Exhaust air is silenced.
- * Hook & Loop pad.
- * Lightweight.
- * Adjustable speed.
- * Excenterstroke 2,5mm.
- * Version for connection to central dust extraction (for 32mm hose size).

Related products



AC30A-F03E-B
Modular FRL Unit

Related accessories



50LVJOSY-P
Pad 125mm Multi Hole



ATLUB
Air Tool Oil, 1 litre



Specifications

Brand	RedRoosterIndustrial
RPM	12000
Airconsumption (l/s)	4,9
Weight (kg)	0,7
Airconnection	PT 1/4"
Airpress max. (MPa)	0,63
mm A	213
mm B	104
Hosediameter (mm)	6,5
Spindle	5/16" UNF
Sanding pads	125
Power (kW)	0,3
Safety standard	EN ISO 11148-8
Excenter stroke (mm)	2
Vibration standard	EN ISO 28927-3
Vibration value (m/s ²)	3
Vibration uncertainty (m/s ²)	0,94
Sound standard	ISO 15744
Sound pressure (dB(A))	73
Sound uncertainty (dB(A))	3
EAN	8717981197118

