

IMPULSE WRENCH 3/8"

YLA70E

Yokota impulse wrenches are widely used for tightening jobs in the assembly industry, where accurate torque tolerances are necessary. Impulse tools are light, powerful, small and very importantly, have no kick-back. Pistol model with double chamber airmotor. Extremely low weight and adapted for use with non-lubricated air.

Related products



AC30A-F03E-B
Modular FRL Unit

Related accessories

0189-0029-00-00

Rubber protection cover YLA60 /70



61022-TH002
Tool Holder, diameter 47mm



ATLUB
Air Tool Oil, 1 litre



Specifications

Brand	Yokota
Bolt capacity (mm)	6 - 8
RPM	7000
Torque (Nm)	20 - 35
Weight (kg)	0,8
Airconnection	PT 1/4"
Airpress max. (MPa)	0,63
Airconsumption fullload (l/s)	5,5
mm A	132
mm B	22
Hosediameter (mm)	6,5
Square Drive / Hexagon	3/8"
Safety standard	EN ISO 11148-6
Air consumption no load (l/s)	6,1
Formal Capacity	20 - 35
Formal Serie From	0N0027
Vibration standard	EN ISO 28927-2
Vibration value (m/s ²)	< 2,5
Vibration uncertainty (m/s ²)	1
Sound standard	ISO 15744
Sound pressure (dB(A))	74
Sound uncertainty (dB(A))	3
Product Group	Impulse Wrenches
Sales Group	002
UNSPSC number	27131501
Eclass number	21061206
EAN	8717981129539

