YOKOTA
CONTROLLED PRECISION IN TIGHTENING

CORDLESS SYSTEM WRENCH 40~60NM
YS-Z950

YOKOTA impulse wrenches are widely used for tightening jobs in the assembly industry, where accurate torque tolerances are necessary. Impulse tools are light, powerful, small and very importantly, have no kick-back. Product liability is essential to carmakers. All tightened joints have to be correct. For this reason bolted joints must be documented and, tightened with the right clamp force. For this, you need an impulse wrench (with a built-in torque transducer and angle-encoder on the main shaft) connected to a controller. If the controller establishes that tightened joints do not meet specifications, it can give a line-stop signal and the joints can be checked manually.
Characteristics:
- **Freedom of movement by use of batteries**
- **Low weight / torque ratio**
- **High speed fastening**
- **Acoustic and LED signals for tightening status indication**
- **No Kickback**
- **Brushless DC drive, RPM freely adjustable**
- **Hybrid technology**
- **100% check on tightening abnormalities**



Related products


BPL-1820
Battery for YS-E, YZ-N and YZ-T ser


WU-2
Wireless controller YS-Z wrench


PC-2
Programming console


DS-2
Display


BC2075MX
Battery Charger for BPL-1820

Related accessories


0446-1801-00-00
Hanger clip YOKOTA cordless wrench


0446-0017-00-00
Hanger YOKOTA


61022-TH005
Tool Holder


0446-0029-00-01
Rubber protection cover Battery


61022-TH002
Tool Holder, diameter 47mm

0485-0029-00-00
Rubber protection cover YS-Z950

Specifications

Brand	**Yokota**
Square Drive	**3/8"**
Bolt capacity (mm)	**10**
RPM	**1200 - 4800**
Torque (Nm)	**40 ~ 60**
Weight w/o battery (kg)	**1,53**
mm A	**226**
mm B	**26**
Battery voltage (Volt)	**18**
Battery type Li-ion….(Ah)	**2,0**
Vibration standard	**EN ISO 28927-2**
Vibration value (m/s²)	**< 2,5**
Vibration uncertainty (m/s²)	**1**
Sound standard	**ISO 15744**
Sound pressure (dB(A))	**79**
Sound uncertainty (dB(A))	**3**
EAN	**8717981439447**

