RED ROOSTER
LEADING IN POWER TOOL SOLUTIONS

# 18V SCREWDRIVER 1/4 HEX SHUT-OFF
# RRI-BS12H2

RED ROOSTER Cordless shut-off screwdriver. Very well suited for assembly applications with a need of good torque accuracy. Especially in areas where cables and hoses impede handling flexibility, such as interiors of cars, coaches and trains. Contactless trigger and forward / reverse switch for a long lifetime.
Characteristics:
- Brushless motor
- 18 Volt Lithium-Ion battery
- LED status indicates OK - NOK - REVERSE - BATTERY LOW
- Adjustable torque
- Speed 250 to 800 RPM
- Compact and light weight

Battery (2,5 Ah: BB200D-325; 5,0 Ah: BB200D-350) and charger (B84192B) to be ordered separately




## Related products


BB200D-325
18V 2.5Ah Battery, Li-ion


B74SC180B
Programmer


BB200D-350
18V 5.0Ah Battery, Li-ion


B84192B
18-20V Charger


E86B-VD
Power Cord (EU)

## Related accessories


D39SC180B-1
Suspension Bail


33154-SCEP-04
Lock Nut Yellow


33116-B200D-01
Protection Cover


61022-TH005
Tool Holder


33116-B200D-02
Protection Cover


33154-SCEP-03
Lock Nut Blue


61022-TH003
Tool Holder, diameter 58mm


D54SC#BV
Lock Nut Black


33116-SCEP-01
Protection Cover


00-4507

## Specifications

| | |
|---|---|
| Brand | RedRoosterIndustrial |
| Bolt capacity (mm) | 6 |
| RPM | 250 - 800 |
| Torque (Nm) | 2,5 - 12 |
| Weight w/o battery (kg) | 1,0 |
| Hexagon | 1/4" |
| mm A | 203 |
| mm B | 238 |
| Battery voltage (Volt) | 18 |
| Battery type Li-ion….(Ah) | 2,5 / 5,0 |
| Vibration standard | EN ISO 28927-2 |
| Vibration value (m/s²) | 0,4 |
| Vibration uncertainty (m/s²) | 1,5 |
| Sound standard | ISO 15744 |
| Sound pressure (dB(A)) | 65,6 |
| Sound uncertainty (dB(A)) | 3 |
| EAN | 8717981400638 |

