

# IMPULSE WRENCH 3/8"

## YX-280SE

Yokota impulse wrenches are widely used for tightening jobs in the assembly industry, where accurate torque tolerances are necessary. Impulse tools are light, powerful, small and very importantly, have no kick-back. Straight model.

### Related products



**AC30A-F03E-B**  
Modular FRL Unit



**HTB-0**  
Spring Balancer Hosereel

### Related accessories



**ATLUB**  
Air Tool Oil, 1 litre



### Specifications

Brand	Yokota
Bolt capacity (mm)	6 - 8
RPM	10500
Torque (Nm)	25 - 38
Weight (kg)	1,02
Airconnection	PT 1/4"
Airpress max. (MPa)	0,63
Airconsumption fullload (l/s)	5,0
mm A	232
mm B	23
Hosediameter (mm)	6,5
Square Drive / Hexagon	3/8"
Safety standard	EN ISO 11148-6
Air consumption no load (l/s)	9,1
Vibration standard	EN ISO 28927-2
Vibration value (m/s <sup>2</sup> )	4,1
Vibration uncertainty (m/s <sup>2</sup> )	1
Sound standard	ISO 15744
Sound pressure (dB(A))	83
Sound power (dB(A))	94
Sound uncertainty (dB(A))	3
EAN	8717981114566

