

IMPULSE WRENCH 3/8" SHUT-OFF RRI-BIM15T

RED ROOSTER Cordless shut-off impulse wrench. High tightening speed combined with good accuracy. No reaction forces during the tightening process. Brushless motor for long motor life and high efficiency. No tightening functionality when battery charge is low, thus process safety improves. Very well suited in areas where cables and hoses impede handling flexibility of tools, such as interiors of cars, coaches and trains.

Characteristics:

- Brushless motor
- Lithium-Ion battery (choice for 2,5 Ah or 5,0 Ah capacity)
- LED status indicates: Reverse, OK, NG, Battery low
- Torque adjustable
- Fine-tuning on hardness of the joint, electronically
- Variable speed control with non-contact trigger
- Run-down speed: 4500 RPM

Battery and charger to be ordered separately

Related products



BB200D-325

18V 2.5Ah Battery, Li-ion



B74SC180B





BB200D-350

18V 5.0Ah Battery, Li-ion



B84192B

18-20V Charger



E86B-VD Power Cord (EU)

Related accessories



33116-B200D-01

Protection Cover

C16PW-15

Protection Cover RRI-BIM15



61022-TH005

Tool Holder



33116-B200D-02





B10PW15

Back Panel Cover (ALU)



Specifications

| Brand | RedRoosterIndustrial |
|------------------------------|----------------------|
| Square Drive | 3/8" |
| Bolt capacity (mm) | 6 |
| RPM | 4500 |
| Torque (Nm) | 8 - 15 |
| Weight w/o battery (kg) | 1,16 |
| mm A | 29 |
| mm B | 224 |
| Battery voltage (Volt) | 18 |
| Battery type Li-ion(Ah) | 2,5 / 5,0 |
| Safety standard | EN ISO 11148-6 |
| Vibration standard | EN ISO 28927-2 |
| Vibration value (m/s²) | 4,24 |
| Vibration uncertainty (m/s²) | 1,5 |
| Sound standard | ISO 15744 |
| Sound pressure (dB(A)) | 73,5 |
| Sound uncertainty (dB(A)) | 3 |
| EAN | 8717981326235 |

