

# CORDLESS SHUT-OFF ANGLE WRENCH RRI-BA30BOA H13

RED ROOSTER cordless angle wrench with automatic shut-off. Very well suited for assembly applications with a need of good torque accuracy. Especially in areas where cables and hoses impede handling flexibility, such as interiors of cars, coaches and trains.

**Characteristics:**

- Brushless motor
- 18 Volt Lithium-Ion battery
- Led status indicates OK - NOK - REVERSE - BATTERY LOW
- Adjustable torque (8-17 Nm)
- Speed 450 RPM
- angled open geared offset head with 13 mm Hexagon drive
- Compact and light weight

Battery and charger to be ordered separately

**Related products**

-  **BB200D-325**  
18V 2.5Ah Battery, Li-ion
-  **B74SC180B**  
Programmer
-  **BB200D-350**  
18V 5.0Ah Battery, Li-ion
-  **B84192B**  
18-20V Charger
-  **E86B-VD**  
Power Cord (EU)

**Related accessories**

-  **33116-B200D-01**  
Protection Cover
-  **33116-B200D-02**  
Protection Cover
-  **00-4507**  
Torque Adjust Key RRI screwdriver



**Specifications**

<b>Brand</b>	RedRoosterIndustrial
<b>RPM</b>	450
<b>Torque (Nm)</b>	8 - 17
<b>Weight (kg)</b>	2,1
<b>mm A</b>	480
<b>mm B</b>	87
<b>mm D</b>	13
<b>mm H</b>	21
<b>mm L</b>	40
<b>mm O</b>	10,2
<b>mm R</b>	17
<b>mm W</b>	40
<b>A/F (mm)</b>	13
<b>H1 mm</b>	16
<b>Battery voltage (Volt)</b>	18
<b>Battery type Li-ion....(Ah)</b>	2,5 / 5,0
<b>Vibration standard</b>	EN ISO 28927-2
<b>Vibration value (m/s<sup>2</sup>)</b>	12,1
<b>Vibration uncertainty (m/s<sup>2</sup>)</b>	1,5
<b>Sound standard</b>	ISO 15744
<b>Sound pressure (dB(A))</b>	66,9
<b>Sound uncertainty (dB(A))</b>	3
<b>EAN</b>	8717981357086