

# STRAIGHT GRINDER 125MMX12,7MM TSG-5L

This straight grinder of Toku has double rows of bearings for a long lifetime. The grinder has an integrated speed-regulator for a maximum of safety and the optimal performance in material removal.

**Characteristics:**

- \* Ergonomic design, well balanced
- \* The air-exhaust is directed away from the user
- \* Safety start lever

**Related products**



**AC30A-F03E-B**  
 Modular FRL Unit

**Related accessories**



**ATLUB**  
 Air Tool Oil, 1 litre



**Specifications**

<b>Brand</b>	<b>Toku</b>
<b>RPM</b>	<b>7600</b>
<b>Airconsumption (l/s)</b>	<b>16,6</b>
<b>Weight (kg)</b>	<b>3,08</b>
<b>Sound level (dB(A))</b>	<b>79</b>
<b>Airconnection</b>	<b>PT 3/8"</b>
<b>Airpress max. (MPa)</b>	<b>0,63</b>
<b>mm A</b>	<b>460</b>
<b>mm B</b>	<b>65</b>
<b>Hosediameter (mm)</b>	<b>13</b>
<b>Spindle</b>	<b>5/8"</b>
<b>Power (kW)</b>	<b>1,05</b>
<b>Vibration level (m/s<sup>2</sup>)</b>	<b>1,5</b>
<b>Wheel size (mm)</b>	<b>125 x 19 x 12,7</b>
<b>Safety standard</b>	<b>EN ISO 11148-7</b>
<b>EAN</b>	<b>8717981011339</b>

