



AIR DRYER

IDFA11E-23-K

The SMC IDFA Series of refrigerated air dryers are the result of over 40 years of experience combined with the latest compressed air and refrigeration technology. Built according to international standards and recognized by SMC's BS EN ISO 9001 quality certification. The IDFA Series has thirteen standard models with nominal capacities ranging from 12 – 1.340 m³/h.

FEATURES

- Innovative design ensures a constant +3 degrees °C pressure dew point
- High efficiency heat exchanger
- Environmentally ozone friendly refrigerants
- Conforms to stringent ISO8573-1 standard
- Simple control system with easy to read evaporator gauge
- Compact design for easy installation
- High performance, reliable and trouble-free



Specifications

| | |
|-------------------------------------|---------------------------|
| Brand | SMC |
| Weight (kg) | 28 |
| Refrigerant | R134a |
| Airconnection | Rc 3/4 |
| Airpress max. (MPa) | 0,15 - 1,6 |
| mm A | 270 |
| mm B | 485 |
| mm C | 568 |
| Ambient temp. | 2 - 40 |
| Power cons. (W) | 385 |
| Inlet air temperature | 5 - 50 |
| Power Supply (V) | 1 Phase 230 V AC 50/60 Hz |
| Flowrate at 3°C Pressure dew point | 80 |
| Flowrate at 7°C Pressure dew point | 101 |
| Flowrate at 10°C Pressure dew point | 112 |
| EAN | 8717981034666 |