

# CORDLESS SHUT-OFF ANGLE WRENCH

## RRI-BA10S3

RED ROOSTER cordless angle wrench with automatic shut-off. Very well suited for assembly applications with a need of good torque accuracy. Especially in areas where cables and hoses impede handling flexibility, such as interiors of cars, coaches and trains.

### Characteristics:






- Brushless motor
- Lithium-Ion battery, choice for 2,5Ah or 5,0 Ah capacity
- LED status indicates OK - NOK - REVERSE - BATTERY LOW
- Adjustable torque
- Speed 400 to 1000 RPM
- Compact and light weight

Battery and charger to be ordered separately

### Related products

- |   |  |
|---|--|
|  | <b>BB200D-325</b><br>18V 2.5Ah Battery, Li-ion |
|  | <b>B74SC180B</b><br>Programmer                 |
|  | <b>BB200D-350</b><br>18V 5.0Ah Battery, Li-ion |
|  | <b>B84192B</b><br>18-20V Charger               |
|  | <b>E86B-VD</b><br>Power Cord (EU)              |

### Related accessories

- |   |   |
|---|---|
|  | <b>33116-B200D-01</b><br>Protection Cover           |
|  | <b>61022-TH005</b><br>Tool Holder                   |
|  | <b>33116-B200D-02</b><br>Protection Cover           |
|  | <b>00-4507</b><br>Torque Adjust Key RRI screwdriver |
|  | <b>C16WR</b><br>Protection Cover RRI-BA10-35        |



### Specifications

Brand	RedRoosterIndustrial
Square Drive	3/8"
Bolt capacity (mm)	4 - 5
RPM	400 - 1000
Torque (Nm)	3 - 12
Weight w/o battery (kg)	1,5
mm A	441
mm B	39
Battery voltage (Volt)	18
Battery type Li-ion....(Ah)	2,5 / 5,0
Safety standard	EN ISO 11148-6
Vibration standard	EN ISO 28927-2
Vibration value (m/s <sup>2</sup> )	12,5
Vibration uncertainty (m/s <sup>2</sup> )	1,5
Sound standard	ISO 15744
Sound pressure (dB(A))	73,3
Sound uncertainty (dB(A))	3
EAN	8717981337460

