

CORDLESS SHUT-OFF ANGLE WRENCH

RRI-BA10S3

RED ROOSTER cordless angle wrench with automatic shut-off. Very well suited for assembly applications with a need of good torque accuracy. Especially in areas where cables and hoses impede handling flexibility, such as interiors of cars, coaches and trains.

Characteristics:




- Brushless motor
- Lithium-Ion battery, choice for 2,5Ah or 5,0 Ah capacity
- LED status indicates OK - NOK - REVERSE - BATTERY LOW
- Adjustable torque
- Speed 400 to 1000 RPM
- Compact and light weight

Battery and charger to be ordered separately

Related products

-  **BB200D-325**
20V 2.5Ah Battery, Li-ion
-  **B74SC180B**
Programmer
- BB200D-350**
20V 5.0Ah Battery, Li-ion
- B84192B**
18-20V Charger
- E86B-VD**
Power Cord (EU)

Related accessories

-  **33116-B200D-01**
Protection Cover
-  **61022-TH005**
Tool Holder
-  **33116-B200D-02**
Protection Cover
-  **00-4507**
Torque Adjust Key RRI screwdriver
- C16WR**
Protection Cover RRI-BA10-35



Specifications

| | |
|---|----------------------|
| Brand | RedRoosterIndustrial |
| Square Drive | 3/8" |
| Bolt capacity (mm) | 4 - 5 |
| RPM | 400 - 1000 |
| Torque (Nm) | 3 - 12 |
| Weight w/o battery (kg) | 1,5 |
| mm A | 441 |
| mm B | 39 |
| Battery voltage (Volt) | 20 |
| Battery type Li-ion....(Ah) | 2,5 / 5,0 |
| Safety standard | EN ISO 11148-6 |
| Vibration standard | EN ISO 28927-2 |
| Vibration value (m/s ²) | 12,5 |
| Vibration uncertainty (m/s ²) | 1,5 |
| Sound standard | ISO 15744 |
| Sound pressure (dB(A)) | 73,3 |
| Sound uncertainty (dB(A)) | 3 |
| EAN | 8717981337460 |

