

# VERTICAL GRINDER 230MMX22MM














## 7VC-6500FS

This vertical grinder of Yokota is used in industrial applications and shipyards. The grinder has an integrated speed-regulator for a maximum of safety and the optimal performance in material removal.

**Characteristics:**

- \* Ergonomic design, well balanced
- \* The air-exhaust is silenced
- \* Safety start lever

**Related accessories**

-  1508-0655-00-00  
Outer Wheel Screw
-  9310-3006-00-99  
Rubber Pad (178) With Flange
-  1508-0653-00-03  
Inner Flange
-  8100-5001-00-00  
Twin Wrench
-  8100-4003-00-01  
Hook Wrench
-  9310-3006-00-00  
Rubber pad G-70/7VC-6500/7VC-8500
-  1508-0654-05-05  
Pad Flange
-  1508-0654-00-01  
Outer Flange
-  1508-0653-01-02  
Inner Flange
-  1422-0653-00-99  
Inner Flange
-  ATLUB  
Air Tool Oil, 1 litre
-  8100-5002-00-00  
Twin Wrench G70EF/7VC-6500/7VC-8500
-  1508-0654-00-02  
Outer Flange



**Specifications**

Brand	Yokota
RPM	6500
Airconsumption (l/s)	23,0
Weight (kg)	4,2
Sound level (dB(A))	82
Airconnection	PT 3/8"
Airpress max. (MPa)	0,63
mm A	195
mm B	180
mm C	180
mm D	160
Hosediameter (mm)	13
Spindle	5/8"
Power (kW)	1,74
Vibration level (m/s <sup>2</sup> )	3
Wheel size (mm)	230 x 6 x 22
EAN	8717981085880

