

VERTICAL GRINDER 230MMX22MM

7VC-6500FS

This vertical grinder of Yokota is used in industrial applications and shipyards. The grinder has an integrated speed-regulator for a maximum of safety and the optimal performance in material removal.

Characteristics:











- * Ergonomic design, well balanced
- * The air-exhaust is silenced
- * Safety start lever

Related products



AC40A-F04-D
Modular FRL unit

Related accessories

-  **1508-0655-00-00**
Outer Wheel Screw
-  **9310-3006-00-99**
Rubber Pad (178) With Flange
-  **1508-0653-00-03**
Inner Flange
-  **8100-5001-00-00**
Twin Wrench
-  **8100-4003-00-01**
Hook Wrench
-  **9310-3006-00-00**
Rubber pad G-70/7VC-6500/7VC-8500
-  **1508-0654-05-05**
Pad Flange
-  **1508-0654-00-01**
Outer Flange
-  **1508-0653-01-02**
Inner Flange
-  **1422-0653-00-99**
Inner Flange
-  **ATLUB**
Air Tool Oil, 1 litre
-  **8100-5002-00-00**
Twin Wrench G70EF/7VC-6500/7VC-8500
-  **1508-0654-00-02**
Outer Flange



Specifications

Brand	Yokota
RPM	6500
Airconsumption (l/s)	23,0
Weight (kg)	4,2
Sound level (dB(A))	82
Airconnection	PT 3/8"
Airpress max. (MPa)	0,63
mm A	195
mm B	180
mm C	180
mm D	160
Hosediameter (mm)	13
Spindle	5/8"
Power (kW)	1,74
Vibration level (m/s ²)	3
Wheel size (mm)	230 x 6 x 22
Safety standard	EN ISO 11148-7
EAN	8717981085880

