

# VERTICAL GRINDER 230MMX22MM

## 7VC-6500FS

This vertical grinder of Yokota is used in industrial applications and shipyards. The grinder has an integrated speed-regulator for a maximum of safety and the optimal performance in material removal.

Characteristics:

- \* Ergonomic design, well balanced
- \* The air-exhaust is silenced
- \* Safety start lever

### Related products



AC40A-F04-D

Modular FRL unit

### Related accessories



1508-0655-00-00

Outer Wheel Screw



9310-3006-00-99

Rubber Pad (178) With Flange



1508-0653-00-03

Inner Flange



8100-5001-00-00

Twin Wrench



8100-4003-00-01

Hook Wrench



9310-3006-00-00

Rubber pad G-70/7VC-6500/7VC-8500



1508-0654-05-05

Pad Flange



1508-0654-00-01

Outer Flange



1508-0653-01-02

Inner Flange



1422-0653-00-99

Inner Flange



ATLUB

Air Tool Oil, 1 litre



8100-5002-00-00

Twin Wrench G70EF/7VC-6500/7VC-8500



1508-0654-00-02

Outer Flange



### Specifications

Brand	Yokota
RPM	6500
Airconsumption (l/s)	23,0
Weight (kg)	4,2
Sound level (dB(A))	82
Airconnection	PT 3/8"
Airpress max. (MPa)	0,63
mm A	195
mm B	180
mm C	180
mm D	160
Hosediameter (mm)	13
Spindle	5/8"
Power (kW)	1,74
Vibration level (m/s <sup>2</sup> )	3
Wheel size (mm)	230 x 6 x 22
Safety standard	EN ISO 11148-7
EAN	8717981085880

