

AUTO-SHUT-OFF SCREWDRIVER 4,0~11NM ATEX RRI-SD30512-EX

The RED ROOSTER Shut-Off screwdrivers have a large torque-range, are highly accurate and have a low vibration level. Very ergonomic design and low noise level. The special design of the clutch combines low reaction forces with a high repeatability of the torque. This air tool is designed for the assembly industry, where threaded fasteners are used. ATEX classification: Ex II 2G IIB T4 / Ex II 2D IIIB T135°C.

Characteristics:

- New straight body-design with soft grip
- Reversible
- Rear-exhaust, silenced
- ergonomic grip, push-to-start
- easily adjustable

Related products



AC30A-F03E-B Modular FRL Unit



Spring Balancer Hosereel

Related accessories



00-4507

HTB-0

Torque Adjust Key RRI screwdriver



ATLUB


Air Tool Oil, 1 litre



Specifications

EAN

Brand	RedRoosterIndustrial
Bolt capacity (mm)	6
RPM	500
Torque (Nm)	4,0-11,0
Airconsumption (I/s)	11
Weight (kg)	0,98
Hexagon	1/4"
Sound level (dB(A))	73
Airconnection	PT 1/4"
Airpress max. (MPa)	0,63
mm A	299
mm B	39
mm C	16
mm D	15
Hosediameter (mm)	6,5
Execution	straight - push start
Vibration level (m/s²)	< 2,5
Safety standard	EN ISO 11148-6



8717981460632