

ANGLE GRINDER 100MMX16MM TAG-40FLH

This angled grinder by Toku is used for grinding and cutting. The dead-handle is vibration reduced. The grinder has an integrated speed-setting regulator for maximum safety and optimal speed for best material removal

Characteristics:

- * Ergonomic design, well balanced
- * Compact and lightweight
- * For cutting and grinding purposes
- * Exhaust silenced
- * Low vibration level

Related accessories



2400-046-11
 Dead Handle Vibration Red.

13-40-04-014
 Combi Spanner 14x19



13-17-08-020
 Hex Socket Head Cap Bolt M8X20

42-05-77-171
 Wheel Ring



ATLUB
 Air Tool Oil, 1 litre



Specifications

Brand	Toku
RPM	13000
Airconsumption (l/s)	10,8
Weight (kg)	1,6
Airconnection	PT 3/8"
Airpress max. (MPa)	0,63
mm A	267
mm B	85
mm C	33
mm D	50
Hosediameter (mm)	10
Spindle	M8
Power (kW)	0,67
Wheel size (mm)	100 x (0,8 - 6) x 16
Vibration standard	EN ISO 28927-1
Vibration value (m/s²)	5,9
Vibration uncertainty (m/s²)	1,95
Sound standard	ISO 15744
Sound pressure (dB(A))	92
Sound power (dB(A))	103
Sound uncertainty (dB(A))	3
EAN	8717981031177

