

# ANGLE GRINDER 100MMX16MM TAG-40FLH

This angled grinder by Toku is used for grinding and cutting. The dead-handle is vibration reduced. The grinder has an integrated speed-setting regulator for maximum safety and optimal speed for best material removal

**Characteristics:**

- \* Ergonomic design, well balanced
- \* Compact and lightweight
- \* For cutting and grinding purposes
- \* Exhaust silenced
- \* Low vibrationlevel

**Related products**



**AC30A-F03E-B**  
**Modular FRL Unit**

**Related accessories**



**2400-046-11**  
**Dead Handle Vibration Red.**

**13-40-04-014**  
**Combi Spanner 14x19**



**13-17-08-020**  
**Hex Socket Head Cap Bolt M8X20**

**42-05-77-171**

**Wheel Ring**



**ATLUB**  
**Air Tool Oil, 1 litre**



**Specifications**

<b>Brand</b>	<b>Toku</b>
<b>RPM</b>	<b>13000</b>
<b>Airconsumption (l/s)</b>	<b>10,8</b>
<b>Weight (kg)</b>	<b>1,7</b>
<b>Airconnection</b>	<b>PT 3/8"</b>
<b>Airpress max. (MPa)</b>	<b>0,63</b>
<b>mm A</b>	<b>267</b>
<b>mm B</b>	<b>85</b>
<b>mm C</b>	<b>33</b>
<b>mm D</b>	<b>50</b>
<b>Hosediameter (mm)</b>	<b>10</b>
<b>Spindle</b>	<b>M8</b>
<b>Power (kW)</b>	<b>0,67</b>
<b>Wheel size (mm)</b>	<b>100 x (0,8 - 6) x 16</b>
<b>Safety standard</b>	<b>EN ISO 11148-7</b>
<b>Vibration standard</b>	<b>EN ISO 28927-1</b>
<b>Vibration value (m/s<sup>2</sup>)</b>	<b>5,9</b>
<b>Vibration uncertainty (m/s<sup>2</sup>)</b>	<b>1,95</b>
<b>Sound standard</b>	<b>ISO 15744</b>
<b>Sound pressure (dB(A))</b>	<b>92</b>
<b>Sound power (dB(A))</b>	<b>103</b>
<b>Sound uncertainty (dB(A))</b>	<b>3</b>
<b>EAN</b>	<b>8717981031177</b>

