

MINI AIR CHAIN HOIST 125 KG TCR-125DPE

The RED ROOSTER Mini Air Chain Hoists are besides industrial use also very suitable for "Material Handling". Due to the low weight, these hoists are very suitable for service applications.

Characteristics:

- * Low weight and therefore very mobile, easy mounting
- * TCR-125 only 7 kg, 3 meter lift included
- * Precise variable speed control (cord - and pendant control)
- * Very compact design
- * Robust aluminium housing
- * Air motor is cooled by the exhaust air (internal)
- * Cord control or pendant control
- * Quiet, low noise level, silenced

Related products



4X12RTS

Chain RTS EN 818-7



AC30-F03DM-8-B

Modular FRL Unit



4X12RS60

Chain RS60 Stainless Steel EN818-7



42-02-32-VRC

Pendant Valve Assy (Direct)



Specifications

Brand	RedRooster
Number of chain falls	1
Lowering speed full load (m/min)	14,8
Lowering speed 0-load (m/min)	13
Weight incl. 3m lift (kg)	8,6
Lifting speed full load (m/min)	12,8
Lifting speed 0-load (m/min)	17,2
Chain weight (kg/m)	0,35
Chain (mm)	4,0 x 12,0 RTS
Chainbag/Chainbucket	+
Loadlimiter	-
Airconnection	3/8" BSPT
Airpress max. (MPa)	0,63
Airconsumption fullload (l/s)	13,3
mm A	286
mm B	112
mm C	174
mm D	130
mm E	305
mm F	71
mm G	21
mm H	19
mm J	33
mm K	21
mm L	-
mm M	2310
mm N	375
mm P	124
mm X	40
mm Z	170
Hosediameter (mm)	13
SMC Airtreatment unit	AC30-F03DM-8-B
Capacity (kg)	125