

STRAIGHT GRINDER 65MMX9,5MM GS-2EFS

This straight grinder of Yokota has double rows of bearings for a long lifetime. The grinder has an integrated speed-regulator for a maximum of safety and the optimal performance in material removal.

Characteristics:

- * Ergonomic design, well balanced
- * The air-exhaust is silenced
- * Safety start lever

Related products



AC30A-F03E-B
Modular FRL Unit

Related accessories



1104-0661-01-99
Collet chuck 6mm GS-2EFS/TSG-3L

8081-0008-00-00
Spanner H13



ATLUB
Air Tool Oil, 1 litre



9300-0005-00-01
Grinding Wheel 65X13X9.5



Specifications

Brand	Yokota
RPM	14000
Airconsumption (l/s)	10,0
Weight (kg)	1,3
Airconnection	PT 1/4"
Airpress max. (MPa)	0,63
mm A	350
mm B	51
Hosediameter (mm)	10
Spindle	3/8" x 16
Power (kW)	0,45
Wheel size (mm)	65 x 13 x 9,5
Safety standard	EN ISO 11148-7
Vibration standard	EN ISO 28927-4
Vibration value (m/s ²)	3,4
Vibration uncertainty (m/s ²)	1
Sound standard	ISO 15744
Sound pressure (dB(A))	81
Sound power (dB(A))	92
Sound uncertainty (dB(A))	3
EAN	8717981148387

