

18V -3/8" HEX TRANSDUCERIZED SCREWDRIVER RRI-BCAW16S3

RED ROOSTER Cordless transducerized angle wrench. Very well suited for assembly applications where good torque accuracy is required. 8 programs can be set for both torque and angular displacement. The programs can be easily selected or programmed in a fixed sequence. Contactless trigger and forward / reverse switch for a long lifetime. Repeatability Cm/Cmk > 2 at +/- 7%.


Characteristics:

- Brushless motor
- 18 Volt Lithium-Ion battery
- LED status indicates OK - NOK - REVERSE - BATTERY LOW
- Tightening mode setting – Torque or Angle
- Programmable torque
- Programmable angle limits
- Programmable speed
- Group check / counting
- 8 programs including sequence
- Compact and light weight
- Tightening Data collection by WLAN
- Battery (2,5 Ah: BB200D-325; 5,0 Ah: BB200D-350) and charger (B84192B) to be ordered separately

Related products

-  **DWL-B**
2.4G/5.8G WLAN receiver
-  **BB200D-325**
18V 2.5Ah Battery, Li-ion
-  **BB200D-350**
18V 5.0Ah Battery, Li-ion
-  **B84192B**
18-20V Charger

Related accessories

-  **33116-B200D-01**
Protection Cover
-  **61022-TH005**
Tool Holder
-  **32088-NPA-01**
Cable
-  **33116-B200D-02**
Protection Cover
- 33116-NRA-01**
Protection Cover RRI-BCA16&30



Specifications

| | |
|-----------------------------|----------------------|
| Brand | RedRoosterIndustrial |
| Square Drive | 3/8" |
| Bolt capacity (mm) | 6 |
| RPM | 120 - 600 |
| Torque (Nm) | 5 - 16 |
| Weight w/o battery (kg) | 1,68 |
| mm A | 438,9 |
| mm B | 38 |
| Battery voltage (Volt) | 18 |
| Battery type Li-ion....(Ah) | 2,5 / 5,0 |
| Safety standard | EN ISO 11148-6 |
| Sound standard | ISO 15744 |
| Sound pressure (dB(A)) | < 75 |
| Sound uncertainty (dB(A)) | 3 |
| EAN | 8717981440474 |

