

# AIR PIPE SAW






## RRI-8460

This pipesaw of RED ROOSTER is intended for heavy industrial use.




Characteristics:

- \* Handle bar in rubber
- \* Big diversity of different saw-blades available as per separate order
- \* Safety starting lever

### Related products

	<b>Z22-75</b> Saw Blade 770X28X2.00 mm 12/1
	<b>Z22-29</b> Saw Blade 400X25X1.50 mm 8/1
	<b>Z22-9</b> Saw Blade 200X25X1.50 mm 8/1
	<b>Z22-30</b> Saw Blade 530X28X1.50 mm 12/1
	<b>Z22-31</b> Saw Blade 300X25X1.50 mm 12/1
	<b>Z22-7</b> Saw Blade 400X25X1.50 mm 16/1
	<b>Z22-6</b> Saw Blade 300X25X1.50 mm 16/1
	<b>Z22-10</b> Saw Blade 200X25X1.50 mm 16/1
	<b>Z22-73</b> Saw Blade 600X28X2.00 mm 14/1
	<b>Z22-37</b> Saw Blade 940X32X2.00mm 12/1 HSS
	<b>Z22-74</b> Saw Blade 600X28X2.00 mm 8/1
	<b>Z22-72</b> Saw Blade 500X28X2.00 mm 14/1

### Related accessories

	<b>8460-205-00</b> Pipe Clamp 20"
	<b>8460-201-01</b> Pipe Clamp 12" RRI-8460
	<b>8460-200-00</b> Pipe Clamp 6"



### Specifications

<b>Brand</b>	RedRoosterIndustrial
<b>Airconsumption (l/s)</b>	20
<b>Weight (kg)</b>	8,0
<b>Capacity metal (mm)</b>	45 - 530
<b>Airconnection</b>	BSP 3/4"
<b>Airpress max. (MPa)</b>	0,63
<b>mm A</b>	460
<b>mm B</b>	537
<b>mm C</b>	240
<b>Stroke (mm)</b>	65
<b>Strokes per minute</b>	300
<b>Hosediameter (mm)</b>	19
<b>Power (kW)</b>	1,1
<b>Vibration standard</b>	EN ISO 28927-8
<b>Vibration value (m/s<sup>2</sup>)</b>	6,29
<b>Vibration uncertainty (m/s<sup>2</sup>)</b>	1,12
<b>Sound standard</b>	ISO 15744
<b>Sound pressure (dB(A))</b>	76,8
<b>Sound uncertainty (dB(A))</b>	3
<b>EAN</b>	8717981148448

