

CORDLESS SHUT-OFF ANGLE WRENCH

RRI-BA30S3

RED ROOSTER cordless angle wrench with automatic shut-off. Very well suited for assembly applications with a need of good torque accuracy. Especially in areas where cables and hoses impede handling flexibility, such as interiors of cars, coaches and trains.

Characteristics:





- Brushless motor
- Lithium-Ion battery, choice for 2,5 Ah or 5,0 Ah battery
- LED status indicates OK - NOK - REVERSE - BATTERY LOW
- Adjustable torque
- Speed 250 to 450 RPM
- Compact and light weight

Battery and charger to be ordered separately

Related products

- | | |
|---|--|
|  | BB200D-325
18V 2.5Ah Battery, Li-ion |
|  | B74SC180B
Programmer |
|  | BB200D-350
18V 5.0Ah Battery, Li-ion |
|  | B84192B
18-20V Charger |
|  | E86B-VD
Power Cord (EU) |

Related accessories

- | | |
|---|---|
|  | 33116-B200D-01
Protection Cover |
|  | 61022-TH005
Tool Holder |
|  | 33116-B200D-02
Protection Cover |
|  | 00-4507
Torque Adjust Key RRI screwdriver |
| | C16WR
Protection Cover RRI-BA10-35 |



Specifications

Brand	RedRoosterIndustrial
Square Drive	3/8"
Bolt capacity (mm)	6 - 8
RPM	250 - 450
Torque (Nm)	8 - 30
Weight w/o battery (kg)	1,5
mm A	446
mm B	38
Battery voltage (Volt)	18
Battery type Li-ion....(Ah)	2,5 / 5,0
Safety standard	EN ISO 11148-6
Vibration standard	EN ISO 28927-2
Vibration value (m/s ²)	12,1
Vibration uncertainty (m/s ²)	1,5
Sound standard	ISO 15744
Sound pressure (dB(A))	66,9
Sound uncertainty (dB(A))	3
EAN	8717981337484

