



# AIR DRYER

## IDFA6E-23-K

The SMC IDFA Series of refrigerated air dryers are the result of over 40 years of experience combined with the latest compressed air and refrigeration technology. Built according to international standards and recognized by SMC's BS EN ISO 9001 quality certification. The IDFA Series has thirteen standard models with nominal capacities ranging from 12 – 1.340 m<sup>3</sup>/h.

### FEATURES

- Innovative design ensures a constant +3 degrees °C pressure dew point
- High efficiency heat exchanger
- Environmentally ozone friendly refrigerants
- Conforms to stringent ISO8573-1 standard
- Simple control system with easy to read evaporator gauge
- Compact design for easy installation
- High performance, reliable and trouble-free



### Specifications

Brand	SMC
Weight (kg)	23
Refrigerant	R134a
Airconnection	Rc 3/4
Airpress max. (MPa)	0,15 - 1,6
mm A	270
mm B	455
mm C	498
Ambient temp.	2 - 40
Power cons. (W)	180
Inlet air temperature	5 - 50
Power Supply (V)	1 Phase 230V AC 50/60 Hz
Flowrate at 3°C Pressure dew point	36
Flowrate at 7°C Pressure dew point	46
Flowrate at 10°C Pressure dew point	50
EAN	8717981054787