

# 18V 1/4 HEX TRANSDUCERIZED SCREWDRIVER **RRI-BCPW16H2**

RED ROOSTER Cordless transducerized screwdriver. Very well suited for assembly applications where good torque accuracy is required. 8 programs can be set for both torque and angular displacement. The programs can be easily selected or programmed in a fixed sequence. Contactless trigger and forward / reverse switch for a long lifetime. Repeatability Cm/Cmk > 2 at +/-7%.

#### Characteristics:

- Brushless motor
- 18 Volt Lithium-Ion battery
- LED status indicates OK NOK REVERSE BATTERY LOW
- Tightening mode setting Torque or Angle
- Programmable torque
- Programmable angle limits
- Programmable speed
- Group check / counting
- 8 programs including sequence
- Compact and light weight
- Tightening Data collection by WLAN
- Battery (2,5 Ah: BB200D-325; 5,0 Ah: BB200D-350) and charger (B84192B) to be ordered separately

### **Related products**



2.4G/5.8G WLAN receiver



BB200D-325

BB200D-350

DWL-B



18V 2.5Ah Battery, Li-ion



18V 5.0Ah Battery, Li-ion



B84192B

18-20V Charger

## **Related accessories**



D39SC180B-1

**Suspension Bail** 



33116-B200D-01 **Protection Cover** 



61022-TH005



**Tool Holder** 



32088-NPA-01 Cable



33116-B200D-02



**Protection Cover** 



61022-TH003

Tool Holder, diameter 58mm

33116-NPA-01

**Protection Cover RRI-BCP** 



#### **Specifications**

Brand	RedRoosterIndustria
Bolt capacity (mm)	6
RPM	100 - 500
Torque (Nm)	5 - 16
Weight w/o battery (kg)	1,01
Hexagon	1/4"
mm A	202,5
mm B	240,5
Battery voltage (Volt)	18
Battery type Li-ion(Ah)	2,5 / 5,0
Safety standard	EN ISO 11148-6
Sound standard	ISO 15744
Sound pressure (dB(A))	< 75
Sound uncertainty (dB(A))	3
EAN	8717981440375

