

TORQUE WRENCH PRESET 10~60NM WPEMH960BSN

FEATURES

- Accuracy: Torque: CW $\pm$ 4% from 20% to 100% of capacity;
Angle: ($\pm$ 1% of reading) + ($\pm$ 1° @ angular speed of 10°/s~180°/s) + ($\pm$ 1° of test fixture)
 - LCD screen display, convenient for real-time viewing. The wrench can be adjusted against the displayed torque value.
 - Maintaining the Click audible alarm feature of the mechanical wrench.
 - 4 Torque units are available: N.m, Ft.lb, In.lb, Kg.cm
 - First peak value mode
 - Adjustable mechanism to set the torque value setting, and minimum angle value can be set in the system to prevent the operator from operating the same screw repeatedly.
 - Peak value and judgment light status remain displayed after unloading.
 - WLAN Server software can receive instant data from 24 wrenches working at the same time and record the information. Each screen can observe 12 wrenches.
- Version with barcode scanner.

Related accessories



DH92160
End fitting 9x12 Ratchet 3/8



OH910
End fitting 9x12, Open End 10 mm



DCQ6232
Setting tool (M) PCH models



BQH914S
9x12 Ring Ratchet End 14 mm



QH912
End fitting 9x12, Ring End A/F 12mm



QOH913
9x12 Open Ring End 13mm



OH911A15
End fitting 9x12, Open End 11 mm an



Specifications

Brand	NovaTork
Torque (Nm)	10 ~ 60
Weight (kg)	0,66
insert tool (mm)	9x12
mm D	24
L mm	296
EAN	8717981475803