

# AUTO-SHUT-OFF SCREWDRIVER 0,8~3,5NM ATEX RRI-SD10903-EX

The RED ROOSTER Shut-Off screwdrivers have a large torque-range, are highly accurate and have a low vibration level. Very ergonomic design and low noise level. The special design of the clutch combines low reaction forces with a high repeatability of the torque. This air tool is designed for the assembly industry, where threaded fasteners are used. ATEX classification: Ex II 2G IIB T4 / Ex II 2D IIIB T135°C.

### **Characteristics:**

- New straight body-design with soft grip
- Reversible
- Rear-exhaust, silenced
- ergonomic grip, push-to-start
- easily adjustable

# **Related products**



AC30A-F03E-B Modular FRL Unit



**Spring Balancer Hosereel** 

## Related accessories



00-4507

HTB-0

**Torque Adjust Key RRI screwdriver** 



ATLUB


Air Tool Oil, 1 litre



# **Specifications**

EAN

Brand	RedRoosterIndustrial
Bolt capacity (mm)	4
RPM	900
Torque (Nm)	0,8 - 3,5
Airconsumption (I/s)	8,5
Weight (kg)	0,69
Hexagon	1/4"
Sound level (dB(A))	73
Airconnection	PT 1/4"
Airpress max. (MPa)	0,63
mm A	258
mm B	36
mm C	16
mm D	15
Hosediameter (mm)	6,5
Execution	Straight - push start
Vibration level (m/s²)	< 2,5
Safety standard	N ISO 11148-6



8717981460540