

TORQUE WRENCH PRESET 50~300NM WPEMH14300BSN

FEATURES

- Accuracy: Torque: CW $\pm$ 4% from 20% to 100% of capacity;
Angle: ($\pm$ 1% of reading) + ($\pm$ 1° @ angular speed of 10°/s~180°/s) +($\pm$ 1° of test fixture)
 - LCD screen display, convenient for real-time viewing. The wrench can be adjusted against the displayed torque value.
 - Maintaining the Click audible alarm feature of the mechanical wrench.
 - 4 Torque units are available: N.m, Ft.lb, In.lb, Kg.cm
 - First peak value mode
 - Adjustable mechanism to set the torque value setting, and minimum angle value can be set in the system to prevent the operator from operating the same screw repeatedly.
 - Peak value and judgment light status remain displayed after unloading.
 - WLAN Server software can receive instant data from 24 wrenches working at the same time and record the information. Each screen can observe 12 wrenches.
- Version with barcode scanner.

Related accessories



OH1411

End fitting 14x18, Open End 11 mm



QOH1424

14x18, Open Ring End 24mm



QH1417

End fitting 14x18, Ring End A/F 17mm



DCQ6231

Setting tool PCH models



Specifications

Brand	NovaTork
Torque (Nm)	50 ~ 300
Weight (kg)	1,28
insert tool (mm)	14x18
mm D	32
L mm	580
EAN	8717981475834