RED ROOSTER
LEADING IN POWER TOOL SOLUTIONS

# COMPOSITE IMPACT WRENCH RRI-3700MK

This impact wrench by RED ROOSTER has an excellent weight/power ratio. The RRI-3700MK is developed for assembly- and disassembly applications. The revolutionary Mechoneer impact mechanism gives high energy levels per impact. The Mechoneer impact mechanism combines the hitting strength of a Twin Hammer with the durability advantage of the closed hammer mechanism. On top of that, it is greased fully, which results in low vibration levels and low sound pressure. The tool is suitable for industrial use. The high RPM air motor builds up the desired torque levels very fast.
Breakloose torque: 3.390 Nm.

Characteristics:
- Ergonomic design, well balanced
- Compact design
- Mechoneer Impact mechanism
- Power adjustable, 3 positions, integrated in Forward/Reverse button
- Dead handle 360 degrees adjustable



## Related accessories



ATLUB
Air Tool Oil, 1 litre



DOESR-3
Ret Ring 1"

## Specifications

| | |
|---|---|
| Brand | RedRoosterIndustrial |
| Square Drive | 1" |
| Version | R+H |
| Bolt capacity (mm) | 36 |
| Impact mechanism | Mechoneer |
| RPM | 6000 |
| Torque (Nm) | 2700 |
| Force adjustment | R/L 3 Pos |
| Airconsumption (l/s) | 20 |
| Weight (kg) | 9,0 |
| Airconnection | PT 1/2" |
| Airpress max. (MPa) | 0,63 |
| mm A | 350 |
| mm B | 62 |
| Hosediameter (mm) | 13 |
| Vibration standard | EN ISO 28927-2 |
| Vibration value (m/s²) | 12,7 |
| Vibration uncertainty (m/s²) | 1,75 |
| Sound standard | ISO 15744 |
| Sound pressure (dB(A)) | 108 |
| Sound uncertainty (dB(A)) | 3 |
| EAN | 8717981418923 |

