

# IMPACT WRENCH 1/2"

## RR-160H

This 1/2" impact wrench by RED ROOSTER has a Dynapact impact mechanism and has a switch with 4 steps for selecting the torque when the direction of rotation is to the right. When turning to the left, the maximum power is always delivered. With the RR-160H you have a well-balanced all-round machine of the highest quality that is effortless to operate with one hand.

### Characteristics:

- Ergonomic design, well balanced
- Exhaust through isolated grip

### Related products

	<b>D0605201003</b>
	Impact Socket Set 1/2" 10-parts
	<b>D0611260501</b>
	Impact Socket Set 1/2" protected 5-parts
	<b>D069523108</b>
	Impact Socket Set 1/2" deep 10-parts
	<b>D00012-0-286</b>
	Impact Socket Set 1/2" Lug Nut 7-parts
	<b>AC30A-F03E-D</b>
	Frl Unit
	<b>D061120310</b>
	Socket Set Wheel Nut Deep 1/2" 17/19/21

### Related accessories

	<b>ATLUB</b>
	Air Tool Oil, 1 litre



### Specifications

<b>Brand</b>	<b>RedRooster</b>
<b>Square Drive</b>	<b>1/2"</b>
<b>Version</b>	<b>R</b>
<b>Bolt capacity (mm)</b>	<b>16</b>
<b>Impact mechanism</b>	<b>Dynapact</b>
<b>RPM</b>	<b>8000</b>
<b>Torque (Nm)</b>	<b>580</b>
<b>Force adjustment</b>	<b>R/L 4 Stufen</b>
<b>Airconsumption (l/s)</b>	<b>7,0</b>
<b>Weight (kg)</b>	<b>2,3</b>
<b>Airconnection</b>	<b>PT 1/4"</b>
<b>Airpress max. (MPa)</b>	<b>0,63</b>
<b>mm A</b>	<b>185</b>
<b>mm B</b>	<b>30</b>
<b>Hosediameter (mm)</b>	<b>10</b>
<b>Safety standard</b>	<b>EN ISO 11148-6</b>
<b>Max. breakaway torque (Nm)</b>	<b>1300</b>
<b>Vibration standard</b>	<b>EN ISO 28927-2</b>
<b>Vibration value (m/s<sup>2</sup>)</b>	<b>9,5</b>
<b>Vibration uncertainty (m/s<sup>2</sup>)</b>	<b>3,1</b>
<b>Sound standard</b>	<b>ISO 15744</b>
<b>Sound pressure (dB(A))</b>	<b>86</b>
<b>Sound power (dB(A))</b>	<b>104,9</b>
<b>Sound uncertainty (dB(A))</b>	<b>3</b>
<b>EAN</b>	<b>871798100272</b>

