

IMPACT WRENCH 1/2"

RR-160H

This 1/2" impact wrench by RED ROOSTER has a Dynapact impact mechanism and has a switch with 4 steps for selecting the torque when the direction of rotation is to the right. When turning to the left, the maximum power is always delivered. With the RR-160H you have a well-balanced all-round machine of the highest quality that is effortless to operate with one hand.


Characteristics:

- Ergonomic design, well balanced
- Exhaust through isolated grip

Related products

-  **DO605201003**
Impact Socket Set 1/2" 10-parts
-  **DO611260501**
Impact Socket Set 1/2" protected 5-parts
-  **DO69523108**
Impact Socket Set 1/2" deep 10-parts
-  **DO0012-0-286**
Impact Socket Set 1/2" Lug Nut 7-parts
-  **DO61120310**
Socket Set Wheel Nut Deep 1/2" 17/19/21"

Related accessories

-  **ATLUB**
Air Tool Oil, 1 litre



Specifications

| | |
|---|----------------|
| Brand | RedRooster |
| Square Drive | 1/2" |
| Version | R |
| Bolt capacity (mm) | 16 |
| Impact mechanism | Dynapact |
| RPM | 8000 |
| Torque (Nm) | 580 |
| Force adjustment | R/L 4 Standen |
| Airconsumption (l/s) | 7,0 |
| Weight (kg) | 2,3 |
| Airconnection | PT 1/4" |
| Airpress max. (MPa) | 0,63 |
| mm A | 185 |
| mm B | 30 |
| Hosediameter (mm) | 10 |
| Safety standard | EN ISO 11148-6 |
| Max. breakaway torque (Nm) | 1300 |
| Vibration standard | EN ISO 28927-2 |
| Vibration value (m/s ²) | 9,5 |
| Vibration uncertainty (m/s ²) | 3,1 |
| Sound standard | ISO 15744 |
| Sound pressure (dB(A)) | 86 |
| Sound power (dB(A)) | 104,9 |
| Sound uncertainty (dB(A)) | 3 |
| EAN | 8717981000272 |

