

TORQUE WRENCH PRESET 6~30NM WPEMH930

FEATURES

- Accuracy: Torque: CW $\pm 4\%$ from 20% to 100% of capacity;
Angle: ($\pm 1\%$ of reading) + ($\pm 1^\circ$ @ angular speed of 10°/s~180°/s) + ($\pm 1^\circ$ of test fixture)
- LCD screen display, convenient for real-time viewing. The wrench can be adjusted against the displayed torque value.
- Maintaining the Click audible alarm feature of the mechanical wrench.
- 4 Torque units are available: N.m, Ft.lb, In.lb, Kg.cm
- First peak value mode
- Adjustable mechanism to set the torque value setting, and minimum angle value can be set in the system to prevent the operator from operating the same screw repeatedly.
- Peak value and judgment light status remain displayed after unloading.
- WLAN Server software can receive instant data from 24 wrenches working at the same time and record the information. Each screen can observe 12 wrenches.

Related accessories



QH911

End fitting

BQH915S

9x12 Ring Ratchet End 15 mm



DCQ6232

Setting tool (M) PCH models



OH910A15

End fitting 9x12, Open End 10 mm an



OH97

End fitting 9x12, Open End 7 mm

QOH913

9x12 Open Ring End 13mm



Specifications

Brand	NovaTork
Torque (Nm)	6 ~ 30
Weight (kg)	0,55
insert tool (mm)	9x12
mm D	24
L mm	248
EAN	8717981443789