

## TORQUE WRENCH PRESET 6~30NM WPEMH930

### FEATURES

- Accuracy: Torque: CW±4% from 20% to 100% of capacity;  
Angle: ( ±1% of reading) + ( ±1° @ angular speed of 10°/s~180°/s) +( ±1° of test fixture)
- LCD screen display, convenient for real-time viewing. The wrench can be adjusted against the displayed torque value.
- Maintaining the Click audible alarm feature of the mechanical wrench.
- 4 Torque units are available: N.m, Ft.lb, In.lb, Kg.cm
- First peak value mode
- Adjustable mechanism to set the torque value setting, and minimum angle value can be set in the system to prevent the operator from operating the same screw repeatedly.
- Peak value and judgment light status remain displayed after unloading.
- WiFi Server software can receive instant data from 24 wrenches working at the same time and record the information. Each screen can observe 12 wrenches.

### Related accessories



**QH911**

End fitting

**BQH915S**

9x12 Ring Ratchet End 15 mm



**OH910A15**

End fitting 9x12, Open End 10 mm an



**OH97**

End fitting 9x12, Open End 7 mm

**QOH913**

9x12 Open Ring End 13mm



### Specifications

Brand	NovaTork
Torque (Nm)	6 ~ 30
Weight (kg)	0,55
insert tool (mm)	9x12
mm D	24
L mm	248
EAN	8717981443789