

# AUTO-SHUT-OFF SCREWDRIVER RRI-SA21704

The RED ROOSTER Shut-Off screwdrivers have a large torque-range, are highly accurate and have a low vibration level. Very ergonomic design and low noise level. The special design of the clutch combines low reaction forces with a high repeatability of the torque. This air tool is designed for the assembly industry, where threaded fasteners are used.

**Characteristics:**

- \* New angled body-design with soft grip
- \* Reversible
- \* Rear-exhaust, silenced
- \* ergonomic grip, lever start
- \* easily adjustable

**Related products**



**AC30A-F03E-B**  
Modular FRL Unit

**Related accessories**



**00-4507**  
Torque Adjust Key RRI screwdriver



**ATLUB**  
Air Tool Oil, 1 litre



**Specifications**

<b>Brand</b>	RedRoosterIndustrial
<b>Bolt capacity (mm)</b>	4
<b>RPM</b>	1700
<b>Torque (Nm)</b>	1,0 - 3,5
<b>Airconsumption (l/s)</b>	10
<b>Weight (kg)</b>	1,02
<b>Hexagon</b>	1/4"
<b>Airconnection</b>	PT 1/4"
<b>Airpress max. (MPa)</b>	0,63
<b>mm A</b>	314
<b>mm B</b>	29
<b>mm C</b>	16,1
<b>mm D</b>	.
<b>mm E</b>	12
<b>Hosediameter (mm)</b>	6,5
<b>Execution</b>	Angle
<b>Safety standard</b>	EN ISO 11148-6
<b>Vibration standard</b>	EN ISO 28927-2
<b>Vibration value (m/s<sup>2</sup>)</b>	0,5
<b>Vibration uncertainty (m/s<sup>2</sup>)</b>	0,54
<b>Sound standard</b>	ISO 15744
<b>Sound pressure (dB(A))</b>	69,2
<b>Sound uncertainty (dB(A))</b>	3
<b>EAN</b>	8717981279111

