

# ROCK DRILL (22X82) TJ-15SV SBS

This vibrationreduced rockdrill of Toku has a latch as retainer. Applicable for time-consuming jobs. High blow-energy. To be used in construction sites and renovations.

**Characteristics:**

- \* Ergonomic design, well balanced
- \* Compact quality tool
- \* Equipped with exhaust muffler



**Specifications**

<b>Brand</b>	Toku
<b>RPM</b>	250
<b>Airconsumption (l/s)</b>	26
<b>Weight (kg)</b>	17,4
<b>Shank size (mm)</b>	H^22 x 82
<b>Airconnection</b>	PT 3/4"
<b>Airpress max. (MPa)</b>	0,63
<b>mm A</b>	468
<b>mm B</b>	340
<b>Stroke (mm)</b>	45
<b>Strokes per minute</b>	2450
<b>Energy (J/Stroke)</b>	44,7
<b>Hosediameter (mm)</b>	19
<b>Piston (mm)</b>	54
<b>Safety standard</b>	EN ISO 11148-5
<b>Vibration standard</b>	EN ISO 28927-10
<b>Vibration value (m/s<sup>2</sup>)</b>	10,2
<b>Vibration uncertainty (m/s<sup>2</sup>)</b>	1,51
<b>Sound standard</b>	ISO 15744
<b>Sound pressure (dB(A))</b>	111
<b>Sound power (dB(A))</b>	122
<b>Sound uncertainty (dB(A))</b>	3
<b>EAN</b>	8717981163960

