

## IMPACT WRENCH 1" MI-3800PR

This industrial impact wrench by Toku has proven capabilities. The MI-3800PR is developed for tightening and untightening applications. The closed hammer mechanism can virtually not be damaged hence applicable for heavy duty applications. The energy is directly converted to the anvil for maximum power and minimal maintenance. The tool is suitable for use in the industry. Characteristics:

- \* Ergonomic design, well balanced
- \* Compact and lightweight
- \* Power adjustable, 4 positions
- \* Exhaust through rotating silencer

## **Related products**



D00100-1-007

Impact Socket Set Long 1" 7-parts



AC40A-F04-D Frl Unit

## **Related accessories**



ATLUB

Air Tool Oil, 1 litre



DOESR-3 Ret Ring



## **Specifications**

Brand Toku
Square Drive 1"
Version R+H
Bolt capacity (mm) 36

Impact mechanism Gesloten Hamer

RPM 4500 Torque (Nm) 2100

Force adjustment R/L 4 Standen

 Airconsumption (I/s)
 15

 Weight (kg)
 9,3

 Airconnection
 PT 1/2"

 Airpress max. (MPa)
 0,63

 mm A
 281

 mm B
 55

 Hosediameter (mm)
 13

Safety standard EN ISO 11148-6 Vibration standard EN ISO 28927-2

Vibration value (m/s²) 15,5

Vibration uncertainty (m/s²) 2,03

Sound standard ISO 15744

Sound pressure (dB(A)) 94

Sound power (dB(A)) 105

Sound uncertainty (dB(A)) 3

EAN 8717981000210

