

IMPACT WRENCH 1" MI-3800PR

This industrial impact wrench by Toku has proven capabilities. The MI-3800PR is developed for tightening and untightening applications. The closed hammer mechanism can virtually not be damaged hence applicable for heavy duty applications. The energy is directly converted to the anvil for maximum power and minimal maintenance. The tool is suitable for use in the industry.

Characteristics:

- * Ergonomic design, well balanced
- * Compact and lightweight
- * Power adjustable, 4 positions
- * Exhaust through rotating silencer

Related products



D00100-1-007
 Socketset Long 1" 7-Parts



AC40A-F04-D
 Modular FRL unit

Related accessories



ATLUB
 Air Tool Oil, 1 litre



DOESR-3
 Ret Ring



Specifications

Brand	Toku
Square Drive	1"
Version	R+H
Bolt capacity (mm)	36
Impact mechanism	Gesloten Hamer
RPM	4500
Torque (Nm)	2100
Force adjustment	R/L 4 Standen
Airconsumption (l/s)	15
Weight (kg)	9,3
Airconnection	PT 1/2"
Airpress max. (MPa)	0,63
mm A	281
mm B	55
Hosediameter (mm)	13
Safety standard	EN ISO 11148-6
Vibration standard	EN ISO 28927-2
Vibration value (m/s²)	15,5
Vibration uncertainty (m/s²)	2,03
Sound standard	ISO 15744
Sound pressure (dB(A))	94
Sound power (dB(A))	105
Sound uncertainty (dB(A))	3
EAN	8717981000210

