

IMPACT WRENCH 3/4" MI-20PG

This TOKU Impact Wrench has an excellent weigth/power ratio. The MI-20GP is developed for assembly- and disassembly purposes. The Twin-Hammer impact mechanism has a high energy level at each impact and thus suitable for heavy duty application. The energy is brought directly to the drive shaft for maximum power and minimal maintenance. This tool is suitable for industrial use.

Characteristics:

- Ergonomic design, well balanced
- Compact and durable
- Clutch: Twin-Hammer
- Adjustable power, 4 positions
- Exhaust through isolated grip, with silencer

Related products



D0605421001

Impact Socket Set 3/4" deep 10-parts



AC40A-F04-D Frl Unit



DO605401001

Impact Socket Set 3/4" 10-parts

Related accessories



DOESR-2 Ret Ring



ATLUB





DOESR-1 Ret Ring



Specifications

 Brand
 Toku

 Square Drive
 3/4"

 Version
 R+H

 Bolt capacity (mm)
 24

Impact mechanism Twin-Hammer

RPM 5000 Torque (Nm) 1000

Force adjustment R/L 4 standen

 Airconsumption (I/s)
 15

 Weight (kg)
 3,9

 Airconnection
 PT 3/8"

 Airpress max. (MPa)
 0,63

 mm A
 215

 mm B
 38

 Hosediameter (mm)
 10

Safety standard EN ISO 11148-6

Max. breakaway torque (Nm) 2400

Vibration standard EN ISO 28927-2

Vibration value (m/s²) 8,5

Vibration uncertainty (m/s²) 1,34

Sound standard ISO 15744

Sound pressure (dB(A)) 94

Sound power (dB(A)) 105

EAN 8717981380893

Sound uncertainty (dB(A))

