

150MM PALM ORBITAL SANDER

RRI-6150-2NV

This RED ROOSTER palm sander is vibration-reduced. The body has a rubber cover for maximum grip. The simplicity of the construction results in a reliable tool.

Applications in: Car-bodywork, metal- and woodworking industry.

Characteristics:

- * Ergonomic design, well balanced.
- * Exhaust air is silenced.
- * Hook & Loop pad.
- * Lightweight.
- * Adjustable speed.
- * Excenterstroke 2,5mm.

Related accessories



610227V-61

Pad



Specifications

| | |
|---|----------------------|
| Brand | RedRoosterIndustrial |
| RPM | 12000 |
| Airconsumption (l/s) | 4,9 |
| Weight (kg) | 0,6 |
| Airconnection | PT 1/4" |
| Airpress max. (MPa) | 0,63 |
| mm A | 163 |
| mm B | 104 |
| Hosediameter (mm) | 6,5 |
| Spindle | 5/16" UNF |
| Sanding pads | 150 |
| Power (kW) | 0,3 |
| Safety standard | EN ISO 11148-8 |
| Excenter stroke (mm) | 2 |
| Vibration standard | EN ISO 28927-3 |
| Vibration value (m/s ²) | 3,04 |
| Vibration uncertainty (m/s ²) | 0,92 |
| Sound standard | ISO 15744 |
| Sound pressure (dB(A)) | 73 |
| Sound uncertainty (dB(A)) | 3 |
| EAN | 8717981197088 |

