RED ROOSTER
LEADING IN POWER TOOL SOLUTIONS

# IMPACT WRENCH 1/2"
# RR-15P

This RED ROOSTER Impact Wrench is suitable for the Automotive Aftermarket. The RR-15P has a good quality for a very low price. This tool has a very simple designed one-hammer clutch.
Characteristics:
* Ergonomic design, well balanced
* Compact and lightweight
* Clutch: Rocking Dog
* Adjustable power, 4 positions




## Related products


DO605201003
Impact Socket Set 1/2" 10-parts


DO605222601
Impact Socket Set 1/2"deep 26-parts


DO691121301
Impact Socket Set 1/2" & bits 13-parts


DO611260501
Impact Socket Set 1/2" protected 5-parts


DO69523108
Impact Socket Set 1/2" deep 10-parts


DO605202602
Impact Socket Set 1/2" 26-parts


DO0012-0-286
Impact Socket Set 1/2" Lug Nut 7-parts


DO652260701
Impact Socket Set 1/2" triple square


AC30A-F03E-D
Frl Unit


DO61120310
Socket Set Wheel Nut Deep 1/2" 17/19/21

## Related accessories


ATLUB
Air Tool Oil, 1 litre

## Specifications

| | |
|---|---|
| Brand | RedRooster |
| Square Drive | 1/2" |
| Version | R |
| Bolt capacity (mm) | 14 |
| Impact mechanism | 1-Hammer |
| RPM | 6900 |
| Torque (Nm) | 560 |
| Force adjustment | R/L Traploos |
| Airconsumption (l/s) | 8,0 |
| Weight (kg) | 2,4 |
| Airconnection | PT 1/4" |
| Airpress max. (MPa) | 0,63 |
| mm A | 180 |
| mm B | 30 |
| Hosediameter (mm) | 10 |
| Max. breakaway torque (Nm) | 1250 |
| Vibration standard | EN ISO 28927-2 |
| Vibration value (m/s²) | 7,47 |
| Vibration uncertainty (m/s²) | 1,23 |
| Sound standard | ISO 15744 |
| Sound pressure (dB(A)) | 82 |
| Sound power (dB(A)) | 93 |
| Sound uncertainty (dB(A)) | 3 |
| EAN | 8717981000265 |

