

# HIGH TORQUE GEAR WRENCH 250 NM

## RRI-BEC025S

RED ROOSTER Cordless high torque geared wrench. Very well suited for assembly applications with a need of good torque accuracy. Especially in areas where cables and hoses impede handling flexibility. Contactless trigger and forward / reverse switch for a long lifetime. Version with two-hand safety control.

Characteristics:

- Brushless motor
- 36 Volt Lithium-Ion battery
- LED status indicates OK - NOK - REVERSE - BATTERY LOW
- Adjustable torque in 50 steps
- Display shows torque and setting
- automatic reaction arm release

Standard reaction arm is included. Batteries, charger and other accessories must be ordered separately.

### Related accessories

- |   |  |
|---|--|
|  | 31022-GW016<br>Reaction Welding Ring RRI-BEC025      |
|  | SW40-283-0102<br>Hanger                              |
|  | 31084-360F<br>36V Charger                            |
|  | 31022-GW001<br>Reaction Bar RRI-BEC025-250           |
|  | 31022-GW010<br>Reaction Bar RRI-BEC025-250           |
|  | 33257-RRI-BEC025<br>Standard Reaction Bar RRI-BEC025 |
|  | 31022-GW009<br>Reaction Bar RRI-BEC025-250           |
|  | 31022-GW014<br>Sliding Reaction Plate RRI-BEC025     |
|  | BW104<br>Back Up Wrench 12-Pt AF 30 mm, max 3254 Nm  |
|  | Koffer RRI-BEC025<br>Case RRI-BEC025                 |
|  | 31022-GW011<br>Reaction Bar Adapter RRI-BEC025       |
|  | BB360F-350<br>36V 5.0Ah Li-ion Battery               |



### Specifications

Brand	RedRoosterIndustrial
Square Drive	1/2"
Bolt capacity (mm)	12 ~ 18
RPM	700 / 75
Torque (Nm)	50 ~ 250
Weight w/o battery (kg)	2,9
Sound level (dB(A))	< 80
mm A	90
mm B	55
mm C	291
mm D	228
mm E	258
mm F	Ø 58
mm L	36
Battery voltage (Volt)	36
Battery type Li-ion....(Ah)	5,0
EAN	8717981454433

