

IMPULSE WRENCH 3/8" SHUT-OFF WLAN RRI-BIMW35T

RED ROOSTER Cordless shut-off impulse wrench. High tightening speed combined with good accuracy. No reaction forces during the tightening process. Brushless motor for long motor life and high efficiency. No tightening functionality when battery charge is low, thus process safety improves. Very well suited in areas where cables and hoses impede handling flexibility of tools, such as interiors of cars, coaches and trains.

- Characteristics:
- Brushless motor
- Lithium-Ion battery (choice for 2,5 Ah or 5,0 Ah capacity)
- LED status indicates: Reverse, OK, NG, Battery low
- Torque adjustable
- Fine-tuning on hardness of the joint, electronically
- Variable speed control with non-contact trigger
- Run-down speed: 3500 RPM

Battery and charger to be ordered separately

Related products

DWL-B 2.4G/5.8G WLAN receiver BB200D-325 18V 2.5Ah Battery, Li-ion B74SC180B

Programmer BB200D-350

18V 5.0Ah Battery, Li-ion

B84192B

18-20V Charger

Related accessories



33116-B200D-01 **Protection Cover** 61022-TH005 **Tool Holder** 33116-B200D-02 **Protection Cover** B10PW15 **Back Panel Cover (ALU)** C16PW-25 Protection Cover RRI-BIM25/35





Specifications

| Brand | RedRoosterIndustrial |
|------------------------------|----------------------|
| Square Drive | 3/8" |
| Bolt capacity (mm) | 8 |
| RPM | 3500 |
| Torque (Nm) | 22 - 35 |
| Weight w/o battery (kg) | 1,36 |
| mm A | 29 |
| mm B | 234 |
| Battery voltage (Volt) | 18 |
| Battery type Li-ion(Ah) | 2,5 / 5,0 |
| Safety standard | EN ISO 11148-6 |
| Vibration standard | EN ISO 28927-2 |
| Vibration value (m/s²) | 8,875 |
| Vibration uncertainty (m/s²) | 1,5 |
| Sound standard | ISO 15744 |
| Sound pressure (dB(A)) | 74,4 |
| Sound uncertainty (dB(A)) | 3 |
| EAN | 8717981452903 |
| | |

