18V ¼ HEX TRANSDUCER SCREWDRIVER RRI-BCP12H2

RED ROOSTER Cordless transducerized screwdriver. Very well suited for assembly applications where good torque accuracy is required. 8 programs can be set for both torque and angular displacement. The programs can be easily selected or programmed in a fixed sequence. Contactless trigger and forward / reverse switch for a long lifetime. Repeatability Cm/Cmk > 2 at +/- 7%.

Characteristics:

- **Brushless motor**
- **18 Volt Lithium-Ion battery**
- **LED status indicates OK - NOK - REVERSE - BATTERY LOW**
- **Tightening mode setting – Torque or Angle**
- **Programmable torque**
- **Programmable angle limits**
- **Programmable speed**
- **Group check / counting**
- **8 programs including sequence**
- **Compact and light weight**
- **The flat battery pack offers stability**
- **Battery (2,5 Ah: BB200D-325; 5,0 Ah: BB200D-350) and charger (B84192B) to be ordered separately**

Related products



BB200D-325
18V 2.5Ah Battery, Li-ion



BB200D-350
18V 5.0Ah Battery, Li-ion



B84192B
18-20V Charger

Related accessories



D39SC180B-1
Suspension Bail



33116-B200D-01
Protection Cover

766-027-612
Side handle for BCP



61022-TH005
Tool Holder



32088-NPA-01
Cable



33116-B200D-02
Protection Cover



61022-TH003
Tool Holder, diameter 58mm

33116-NPA-01
Protection Cover RRI-BCP



Specifications

Brand	**RedRoosterIndustrial**
Bolt capacity (mm)	**6**
RPM	**150 - 750**
Torque (Nm)	**4 - 12**
Weight w/o battery (kg)	**1,01**
Hexagon	**1/4"**
mm A	**202,5**
mm B	**240,5**
Battery voltage (Volt)	**18**
Battery type Li-ion….(Ah)	**2,5 / 5,0**
Vibration standard	**EN ISO 28927-2**
Vibration value (m/s²)	**0,4**
Vibration uncertainty (m/s²)	**0,1**
Sound standard	**ISO 15744**
Sound pressure (dB(A))	**68**
Sound uncertainty (dB(A))	**3**
EAN	**8717981418657**

