

MINI AIR CHAIN HOIST 250 KG TCR-250DPE

The RED ROOSTER Mini Air Chain Hoists are besides industrial use also very suitable for "Material Handling". Due to the low weight, these hoists are very suitable for service applications.

Characteristics:

- * Low weight and therefore very mobile, easy mounting
- * TCR-250 only 7 kg, 3 meter lift included
- * Precise variable speed control (cord - and pendant control)
- * Very compact design
- * Robust aluminium housing
- * Air motor is cooled by the exhaust air (internal)
- * Cord control or pendant control
- * Quiet, low noise level, silenced

Related products



4X12RTS

Chain RTS EN 818-7



AC30-F03DM-8-B

Frl Unit



4X12RS60

Chain RS60 Stainless Steel EN818-7



42-02-32-VRC

Pendant Valve Assy (Direct)



Specifications

Brand	RedRooster
Number of chain falls	1
Lowering speed full load (m/min)	15,9
Lowering speed 0-load (m/min)	13
Weight incl. 3m lift (kg)	8,6
Lifting speed full load (m/min)	8,1
Lifting speed 0-load (m/min)	17,2
Chain weight (kg/m)	0,35
Chain (mm)	4,0 x 12,0 RTS
Chainbag/Chainbucket	+
Loadlimiter	-
Airconnection	3/8" BSPT
Airpress max. (MPa)	0,63
Airconsumption fullload (l/s)	13,3
mm A	310
mm B	111
mm C	74
mm D	37
mm E	112
mm F	140
mm G	15
mm H	35
mm I	22
mm J	20
mm X	40
mm Z	170
Hosediameter (mm)	13
SMC Airtreatment unit	AC30-F03DM-8-B
Capacity (kg)	250
EAN	8717981060344

