

IMPULSE WRENCH 1/2" YLA110E

Yokota impulse wrenches are widely used for tightening jobs in the assembly industry, where accurate torque tolerances are necessary. Impulse tools are light, powerful, small and very importantly, have no kick-back. Pistol model with double chamber airmotor. Extremely low weight and adapted for use with non-lubricated air.

Related products



AC30A-F03E-B Modular FRL Unit

Related accessories

0190-0029-01-00

Rubber protection cover YLA110



61022-TH003

ATLUB

Tool Holder, diameter 58mm



Air Tool Oil, 1 litre




Yokota

Specifications

Brand

EAN

Bolt capacity (mm)	10 - 12
RPM	6000
Torque (Nm)	65 - 105
Weight (kg)	1,4
Airconnection	PT 1/4"
Airpress max. (MPa)	0,63
Airconsumption fullload (I/s)	9,6
mm A	164
mm B	26
Hosediameter (mm)	9,5
Square Drive / Hexagon	1/2"
Safety standard	EN ISO 11148-6
Air consumption no load (I/s)	13,1
Vibration standard	EN ISO 28927-2
Vibration value (m/s²)	3,1
Vibration uncertainty (m/s²)	1
Sound standard	ISO 15744
Sound pressure (dB(A))	81
Sound power (dB(A))	92



8717981032365