

CHIPPING HAMMER AA-OBR(H)

This Toku chipping hammer is equipped with open screwcap retainer for the chisel. Suitable for intensive use. High energy-level each blow. For construction, renovation and foundries.

Characteristics:

- * Ergonomic design, well balanced.
- * Compact and lightweight.
- * Lefthanders and righthanders can use this tool.

Related products

-  **BEAA-OB-04**
Wide Chisel TL=220 B=50
-  **BEAA-OB-01**
Flat Chisel TL= 220 W=16
-  **BEAA-OB-05**
Wide Chisel TL=220 B=100
-  **BEAA-OB-03**
Flat Chisel TL= 220 B=25
-  **BEAA-OB-06**
Wide Chisel bent TL=220 B=50
-  **BEAA-OB-02 400MM**
Moil Point AA-OB TL=400mm
-  **BEAA-OB-01 400MM**
Flat Chisel For AA-OB TL=400 W=16mm
-  **BEAA-OB-04 540MM**
Wide Chisel TL=540 B=50
-  **BEAA-OB-02**
Moil Point TL= 220



Specifications

Brand	Toku
Airconsumption (l/s)	5,8
Weight (kg)	2,6
Shank size (mm)	H^{12,7} x R¹⁵ x 53
Airconnection	PT 3/8"
Airpress max. (MPa)	0,63
mm A	245
mm B	95
Stroke (mm)	50
Strokes per minute	3600
Energy (J/Stroke)	7,5
Hosediameter (mm)	6,5
Piston (mm)	20
Safety standard	EN ISO 11148-4
Vibration standard	EN ISO 28927-10
Vibration value (m/s²)	9,0
Vibration uncertainty (m/s²)	1,10
Sound standard	ISO 15744
Sound pressure (dB(A))	101
Sound power (dB(A))	112
Sound uncertainty (dB(A))	3
EAN	8717981197026

